

# Product Data Sheet

## SERVO OBM 2T OIL

Low Smoke 2 Stroke Engine oil for Outboard Motors



### Description

Servo OBM 2T Oil is low smoke semi-synthetic two stroke engine oil developed to meet the critical requirements of high performance two stroke engines of marine motors. It is blended from selected base stocks and additives to minimize spark plug fouling and preignition, prevent rusting, minimize deposit formation and provide protection against seizure, scuffing and wear.

### Performance, Features and Benefits

- Low exhaust smoke
- Maintains engine cleanliness
- Minimizes spark plug fouling
- Reduces port deposits and ring sticking
- Prevents seizure and scuffing
- Is easily pumpable by oil injection system
- Low aquatic toxicity properties

### Application

Servo OBM 2T Oil is recommended for lubrication of outboards operating on two stroke engines.

### Approvals / Performance Standards / Recommendations

Meets –

- JASO FC specifications
- API TC Specification

### Typical Physical Characteristics

Parameters	Method	Value
Appearance	Visual	Clear
Flash point COC, deg °C	ASTM D92	112
Pour Point, deg °C	ASTM D97	-15
Kinematic viscosity at 100°C, cSt	ASTM D445	8.6
Kinematic viscosity at 40°C, cSt	ASTM D445	57.3
Viscosity Index	ASTM D2270	124

### Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

15 JUL 2022

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,  
Indian Oil Corporation Ltd.,  
G-9, Ali Yavar Jung Marg, Bandra (E),  
Mumbai – 400051

E-Mail: [servotechserv@indianoil.in](mailto:servotechserv@indianoil.in) or  
[servots@indianoil.in](mailto:servots@indianoil.in) | <https://cx.indianoil.in/>