Product Data Sheet

SERVOKOOL PLUS

Long Life Radiator Coolant Concentrate



Description

ServoKool Plus is a general purpose triple action long life radiator coolant concentrate prepared from selected ingredients to meet the highest Japanese standard and is free from Amines, Borates, Nitrites and Silicates.

Performance, Features and Benefits

- Does not boil and vaporize in the hottest summer or freeze in severe winter.
- Prevents corrosion of radiator coolant and other metal parts of the cooling system.
- Increases cooling efficiency of radiator.
- Reduces maintenance costs and increases radiator life.

Application

ServoKool Plus is recommended for passenger cars, light commercial vehicles, heavy vehicles and heavy earth moving equipment as a radiator coolant concentrate. For desired performance, 30 parts of the fluid is to be diluted with 70 parts of distilled water in most of the vehicles.

Approvals/ Performance Standards/Recommendations

- JIS K 2234 Class 2 specification.
- IS : 5759

Typical Physical Characteristics

ServoKoolPlus	Method		Values
Appearance	Visual		Blue liquid
Density @ 20°C, gm/ml	ASTM D112	22	1.126
Boiling Point, °C	ASTM D11	20	166
Freezing Point			
30% Volume Solution, °C	ASTM D117	77	(-) 15
50% Volume Solution, °C			(-) 35
pH of 30 v/v % solution in distilled water	ASTM D12	37	7.8

Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at https://cx.indianoil.in/. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

18 JULY 2020

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise.Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or: Technical Services Department, Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (E), Mumbai – 400051 E-Mail: servotechserv@indianoil.in or servots@indianoil.in | https://cx.indianoil.in/