

Product Data Sheet

SERVOKOOL READY

Long Life Premixed Radiator Coolant



Description

ServoKool Ready is a general purpose triple action long life ready to use radiator coolant diluted with distilled water to meet the highest Japanese standard. It is free from Amines, Borates, Nitrites and Silicates.

Performance, Features and Benefits

- Bio-degradable and environment friendly.
- Free from Amines, Nitrites, Phosphates, Silicates and Borates.
- Keeps the engine cool.
- Prevents corrosion of radiator coolant and other metal parts of the cooling system.
- Increases cooling efficiency.
- Reduces maintenance costs and increases radiator life.

Application

ServoKool Ready is recommended for passenger cars, light commercial vehicles, heavy vehicles and heavy earth moving equipment as a radiator coolant. Since it is a premixed & diluted coolant, it can be used straight away by topping up in the radiator or expansion bottle.

Approvals/ Performance Standards/Recommendations

- JIS K 2234 Class 2 specification.

Typical Physical Characteristics

Servo Kool Ready	Method	Values
Appearance	Visual	Clear Liquid
Colour	Visual	Blue
Density @ 29.5 °C, gm/ml	ASTM D1122	1.042
Boiling Point, °C	ASTM D1120	103
Freezing Point, °C	ASTM D1177	(-) 15
pH Value (as such)	ASTM D1287	7.8
Water Content %Wt.	ASTM D1123	71

Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

18 JULY 2020

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,
Indian Oil Corporation Ltd.,
G-9, Ali Yavar Jung Marg, Bandra (E),
Mumbai – 400051

E-Mail: servotechserv@indianoil.in or
servots@indianoil.in | <https://cx.indianoil.in/>