

# Product Data Sheet



## Servo Transdex II

Automatic Transmission/ Power Steering Fluid

### Description

Servo Transdex II is formulated with selected base stocks and robust additive components to meet the performance requirements of automatic transmissions and power steering units of many types of vehicles where Dexron IID or Mercon performance is essential. Servo Transdex II is a red dyed transmission fluid having a modified friction characteristics. The fluid is compatible with seal materials generally used in transmission systems.

### Performance, Features and Benefits

- Product has better friction characteristics that provide controlled slip for friction components.
- Enhanced driver comfort with smooth shifting
- Provides better oxidation stability and low temperature flow
- Minimise formation of sludge and varnish, thus maintains the system clean
- Has desired fluid characteristics for smooth operations over a wide range of ambient temperatures
- Efficient operation of power steering units under all conditions
- Protects parts against rusting even during idle period

### Application

Servo Transdex II is recommended for automatic transmission and power steering units of automobiles and light trucks requiring Dexron II Fluid or where Mercon performance is required.

### Approvals / Performance Standards / Recommendations

- Meets 6137-M (Dexron II) of General Motors, U.S.A, ZF-TEML-14A, 02F, 17C, 04D

### Typical Physical Characteristics

Parameter	Method	Value
Appearance	Visual	Clear
Colour	ASTM D1500	Red
Flash point COC, °C,	ASTM D92	221
Pour point, °C,	ASTM D97	-48
Kinematic viscosity @ 100°C, cSt	ASTM D445	7.38
Viscosity Index	ASTM D2270	151
Brookfield Viscosity @ -40°C, cP	ASTM D2983	24295
Density @15°C, Relative g/ml	ASTM D1298	0.8533

### Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

24 NOV 2020

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,  
Indian Oil Corporation Ltd.,  
G-9, Ali Yavar Jung Marg, Bandra (E),  
Mumbai – 400051

E-Mail: [servotechserv@indianoil.in](mailto:servotechserv@indianoil.in) or  
[servots@indianoil.in](mailto:servots@indianoil.in) | <https://cx.indianoil.in/>