

Product Data Sheet

Servo XEE SL 20W-50

Gasoline Engine Oil



Description

Servo XEE SL 20W-50 is a premium long life, high performance and fuel economical engine oil for new generation petrol vehicles. This oil is blended with high viscosity index base stocks that contain additives to meet the highest quality performance and standards.

Performance, Features and Benefits

- Superior wear protection
- Superior deposit control
- Extended component life
- Excellent engine cleanliness
- Lower oil consumption
- Better Fuel Economy
- Catalytic Convertor Compatible

Application

Servo XEE SL 20W-50 is recommended for new generation imported and Indian passenger cars using petrol as a fuel. The oil is also suitable for use in higher ambient temperature zones.

Approvals / Performance Standards / Recommendations

Servo XEE SL 20W-50 meets the performance requirement of API SL

Typical Characteristics

Properties	Method	Value
Appearance	Visual	Clear
Flash point COC , °C	ASTM D 92	232
Pour point , °C	ASTM D 97	-24
Kinematic viscosity at 100°C, cSt	ASTM D 445	18.83
Viscosity Index	ASTM D 2270	131
CCS @ -15°C	ASTM D 5293	6988
Total base number , mg KOH/g	ASTM D 2896	6.19
Foam test; Tend/Stab, ml		0/nil
Seq. I	ASTM D 892	20/nil
Seq. II		0/nil
Seq. III		
Sulfated ash , % wt	ASTM D 874	0.78

Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

12 OCT 2020

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,
Indian Oil Corporation Ltd.,
G-9, Ali Yavar Jung Marg, Bandra (E),
Mumbai – 400051

E-Mail: servotechserv@indianoil.in or
servots@indianoil.in | <https://cx.indianoil.in/>