

# Product Data Sheet

## Servo MTRAC 424

Premium Universal Tractor Transmission Oil



### Description

Servo MTRAC 30 is a formulated with high quality base stocks and advance additive components to meet the performance requirements of tractor transmissions, hydraulics, final drives, and wet breaks applications. It is Universal Tractor Transmission Oil (UTTO) developed to meet the diverse performance requirements of farm tractor lubricants. Product has controlled friction properties for wet brakes, good filterability and antifoam characteristics, protection against rust and corrosion and adequate EP and antiwear properties for maximum durability of the transmission, differential and final drive.

### Performance, Features and Benefits

- Provides excellent lubrication for complete transmission system including hydraulic, power steering, differential & oil immersed brakes
- Provides excellent wear protection and reduces maintenance cost
- Excellent Oxidation and low temperature fluidity
- Widespread fluid application in tractor transmissions, hydraulics, final drives, and wet brakes.
- Product proven for Wet brake noise suppression characteristics
- Product has longer drain credentials (~2000 hrs)

### Application

Servo MTRAC 30 is recommended for use as Universal Tractor Transmission Oil in Tractors with Wet Brake System and in power shift transmissions and torque converters in off-highway equipment. It is tested and approved by various Tractor OEMs.

### Approvals / Performance Standards / Recommendations

- Meets Allison C4, John Deere JD20C/20D, Massey Ferguson M1135, CNH MAT 3525, 3526, CAT TO 2
- SAE 30 grade UTTO
- Approved by M&M for their tractors with Wet Brake system.

### Typical Physical Characteristics

Parameter	Method	Value
Appearance	Visual	Clear
Kinematic Viscosity @ 100°C, cSt	ASTM D445	11.91
Flash Point COC, °C	ASTM D92	220
Pour Point, °C	ASTM D97	(-) 33
Viscosity Index	ASTM D2270	105
Copper strip corrosion @ 150°C, 3 hrs	ASTM D130	1A
Brookfield Viscosity @ -18°C, cP	ASTM D2983	8398

### Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

24 NOV 2020

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,  
Indian Oil Corporation Ltd.,  
G-9, Ali Yavar Jung Marg, Bandra (E),  
Mumbai – 400051

E-Mail: [servotechserv@indianoil.in](mailto:servotechserv@indianoil.in) or  
[servots@indianoil.in](mailto:servots@indianoil.in) | <https://cx.indianoil.in/>