

Product Data Sheet

Servo4T (10W-30/ 20W-40/ 20W-50) TUK TUK

Four-Stroke High Performance Engine Oil for 2/3 Wheeler



Description

Servo 4T is high performance engine oil for 4-stroke 2/3 wheelers. This oil is blended from high viscosity index base stocks and contains suitable additives to meet the stated performance standards.

Performance, Features and Benefits

- Maximizes power output
- Superior performance in terms of oxidation stability
- Excellent wear protection at high temperatures and severe operating conditions.
- Outstanding overall engine cleanliness.
- Enhanced engine life.
- Higher fuel efficiency.
- Potential for oil drain interval up to 5000 Kms.

Application

Servo 4T is recommended for new generation 4-stroke motorcycles, geared scooters and auto rickshaws.

Approvals / Performance Standards / Recommendations

Servo 4T meets the performance requirement of API SL and JASO MA 2 (T903:2016).

Meet API SM specification of Valve Train Wear (VTW).

Servo 4T is suitable for usage in various OEM make vehicles including following:

- M/s Bajaj Auto Ltd.
- M/s TVS Motor Co. Ltd.

Typical Characteristics

Properties	Method	Servo 4T 10W30	Servo 4T	Servo 4T 20W-50 TUKTUK
Flash point COC, °C	ASTM D-92	228	230	232
Pour point, °C	ASTM D-97	-30	-33	-30
Kinematic viscosity at 100 °C, cSt	ASTM D-445	11.1	14.7	18.4
Viscosity Index	ASTM D-2270	142	128	136
Total base number, mg KOH/g	ASTM D-2896	6.15	6.20	6.10
Sulfated ash, % wt	ASTM D-874	0.77	0.79	0.78

Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

23 JULY 2020

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,
Indian Oil Corporation Ltd.,
G-9, Ali Yavar Jung Marg, Bandra (E),
Mumbai – 400051

E-Mail: servotechserv@indianoil.in or
servots@indianoil.in | <https://cx.indianoil.in/>