

Product Data Sheet

SERVO 4T XTRA Oils

Four-Stroke Premium Motorcycle Engine Oils



Description

Servo 4T Xtra is blended with high quality base stocks and synergistic additive system for outstanding detergency, dispersancy, anti-wear and antioxidant performance. Its delicately balanced formulation exceeds tough industry performance standards thus ensuring reliability, emission control, fuel economy and endurance.

Performance, Features and Benefits

- High quality mineral base stocks impart inherently low temperature pumpability
- Formulated with highly shear stable viscosity index modifiers which ensure viscosity control over extreme temperatures
- Enhanced lubrication to help in maintaining maximum power and acceleration
- Optimized wet-clutch performance
- Excellent low temperature flow characteristics minimizing engine wear during start up
- Significant improvement in fuel economy
- Enhanced oil life and longer drain period

Application

Servo 4T Xtra is recommended for all 4-stroke motorcycles including new generation BS VI motorcycles.

Approvals / Performance Standards / Recommendations

Servo 4T Xtra meets the engine performance requirement of API SN and friction performance of JASO MA2 (T903:2016).

Typical Characteristics

Properties	Method	Servo 4T Xtra 10W-30	Servo 4T Xtra (20W-40)	Servo 4T Xtra 20W-50
Kinematic viscosity at 100 °C, cSt	ASTM D445	10.45	14.05	17.90
Viscosity index	ASTM D2270	146	133	142
Total base number, mg KOH/g	ASTM D2896	6.20	6.25	6.20
Flash point COC, °C,	ASTM D92	238	238	236
Pour point, °C	ASTM D97	-36	-36	-36
HTHS at 150 °C, cP	ASTM D5481	3.15	4.05	4.80

Health, Safety & Environment

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or at <https://cx.indianoil.in/>. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.

18 MAY 2021

All trademarks used herein are trademarks or registered trademarks of Indian Oil Corporation or one of its subsidiaries unless indicated otherwise. Values reported are typical of those obtained with normal production tolerance, and may vary from batch to batch. Due to continual product research and development, the information contained herein is subject to changes without notification. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. All products, services and information supplied are provided under our standard conditions of sale.

For further information, please contact our nearest office or:

Technical Services Department,
Indian Oil Corporation Ltd.,

G-9, Ali Yavar Jung Marg, Bandra (E),
Mumbai – 400051

E-Mail: servotechserv@indianoil.in or
servots@indianoil.in | <https://cx.indianoil.in/>